

City Plastics Pty Ltd  
61 East Street  
Brompton 5007  
South Australia

Ph: (+61) 8, 8346 6500

Fax: (+61) 8, 8346 6711

Email: info@cityplastics.com.au

www.cityplastics.com.au

ABN 20 101 181 793

ACN 101 181 793

- Sheet Plastics
- Cut to size & shape
- CNC Router cutting
- Fabrication
- Vacuum Forming
- Boat Screens & windows
- Signs & Displays
- Engineering Plastics
- Ecoscreen Plastic Lattice
- C/S Acrovyn
- Bld/Lic RL155051

---

## MATERIAL SAFETY DATA SHEET, WELDON 40 Part B

<b>Section 1</b>	<b>Product and Company Identification</b>
------------------	---

City Plastics Pty Ltd  
61 East Street  
BROMPTON 5007  
South Australia

Phone: +61,8,8346 6500

Fax: +61,8,8346 6711

**Material Identification:** Mixture of organic solvents

**Product Name:** WELDON 40, Part B

**Chemical Name:** Benzoyl Peroxide Catalyst

**Product Use:** Adhesive for some plastics

<b>Section 2</b>	<b>Composition/Information on Ingredients</b>
------------------	---

Less than 10% Benzoyl Peroxide in Dibutyl Phthalate

**CAS Number:** 94-36-0 (Benzoyl Peroxide)

84-74-2 (Dibutyl Phthalate)

<b>Section 3</b>	<b>Hazards Identification</b>
------------------	-------------------------------

**Ingestion:** May cause toxic effects.

**Skin:** Prolonged contact may cause allergic rash and itching.

**Eye:** Contact may cause eye irritation.


**Inhalation:** May cause irritation to nose, throat and lungs.

<b>Section 3</b>	<b>First Aid Measures</b>
------------------	---------------------------

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Ingestion:** If swallowed, do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Skin Contact:** Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse.



City Plastics Pty Ltd  
61 East Street  
Brompton 5007  
South Australia  
Ph: (+61) 8, 8346 6500  
Fax: (+61) 8, 8346 6711

## MATERIAL SAFETY DATA SHEET, WELDON 40 Part B

### Section 4 First Aid Measures (Continued)

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

### Section 5 Fire Fighting Measures

**Flash point:** 190°C / 375°F

**Unusual fire, explosion hazards:** Peroxides and decomposition products are flammable and can ignite with explosive force if confined.

**Special fire fighting instructions:** Fire fighters should wear full protective clothing including self-contained breathing apparatus. Fire fighting equipment should be thoroughly decontaminated after use.

**Extinguishing media:** Water spray, dry chemical, foam or carbon dioxide.

### Section 6 Accidental Release Measures

**Spill or release:** Avoid skin contact. Wear appropriate personal protective equipment. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e.g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to stormwater system.

### Section 7 Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from any source of heat or ignition. Detached storage is recommended. Wear special protective equipment where exposures may exceed established exposure levels. Wash hands, face, forearms and neck after use. Wash hands before eating and do not eat, drink, or smoke in workplace.


### Section 8 Exposure Controls/Personal Protection

**Eye:** Use chemical safety goggles and or a full face shield where splashing is possible. Maintain an eye wash fountain or quick drench facilities in work area.

**Skin:** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Neoprene is a recommended material for personal protective equipment. Natural rubber and polyvinyl chloride are not recommended materials for personal protective equipment.

**Ventilation:** Local exhaust at processing area to assure that vapour levels are kept at recommended levels.

**Respirator:** A respirator is recommended at all times, depending on concentration levels a supplied air, full-face piece respirator, air lined hood, or full-face piece self-contained breathing apparatus.



City Plastics Pty Ltd  
61 East Street  
Brompton 5007  
South Australia  
Ph: (+61) 8, 8346 6500  
Fax: (+61) 8, 8346 6711

## MATERIAL SAFETY DATA SHEET, WELDON 40 Part B

### Section 9 Physical and Chemical Properties

**Appearance:** Clear, colourless oily liquid.

**Odour:** Essentially odourless.

**Solubility:** Slightly soluble in water

**Boiling Point:** 340°C / 644°F

**Melting Point:**

**Volatile content %:**

**Specific gravity:** 1.06

### Section 10 Stability and Reactivity

**Stability at room temperature:** Stable under ordinary conditions of use and storage.

**Materials to avoid:** Strong acids, strong bases, strong alkalies, reducing agents, accelerators. Oxidising materials can cause a strong reaction.

**Conditions to avoid:** Thermal decomposition. Contamination.

### Section 11 Toxicological Information

**Chronic toxicity:**

**Medical conditions prone to aggravation by exposure:**

**Carcinogenicity:**

### Section 12 Ecological Information

**Aquatic toxicity:** Toxicity to aquatic life is expected to be low.


**Degradation:** When released into the soil, this material may leach into groundwater.

When released into the soil, this material is expected to quickly evaporate. When released into water, this material may biodegrade to a moderate extent. When released to water, this material is expected to quickly evaporate. This material is not expected to significantly bio accumulate. When released into the air, this material may be moderately degraded by reaction with photo chemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life of greater than 30 days. When released into the air, this material may be removed from the atmosphere to a moderate extent by wet deposition.

### Section 13 Disposal Considerations

**Spill or release:** Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e.g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to stormwater system.

**Waste disposal:** Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to an approved incinerator or disposed in a approved waste facility.



City Plastics Pty Ltd  
61 East Street  
Brompton 5007  
South Australia  
Ph: (+61) 8, 8346 6500  
Fax: (+61) 8, 8346 6711

---

## MATERIAL SAFETY DATA SHEET, WELDON 40 Part B

<b>Section 14</b>	<b>Transport Information</b>
-------------------	------------------------------

All components are classified as Flammable Liquid for the purpose of transport by road or rail. Refer to relevant regulations for storage and transport requirements.

**UN-No:**

**Class:** Flammable Liquid

**Hazchem Code:**

**Packing group:**

<b>Section 15</b>	<b>Regulatory Information</b>
-------------------	-------------------------------

**Poison Schedule:**

<b>Section 16</b>	<b>Other Information</b>
-------------------	--------------------------

**Label Hazard Warning:** WARNING! HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN.

**Label Precautions:** Do not breathe vapour, keep container closed, use only with adequate ventilation, wash thoroughly after handling, keep away from heat and flame, do not get in eyes, on skin, or on clothing.

Prepared by: Steven Cook

Issued: August 1, 2005

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of City Plastics Pty Ltd, accurate and reliable. Such information is offered solely for your consideration, investigation and verification, and it is not suggested or guaranteed that the hazard precautions or procedures mentioned are the only ones, which exist. City Plastics Pty Ltd makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.